

AN 127:36909 CA
TI Drilling fluids
IN Bryan, Edward; Grover, Boyd William; Jones, Christopher Raymond;
Talbot, Robert Eric
PA Albright & Wilson Limited, UK
SO Brit. UK Pat. Appl., 24 pp.
CODEN: BAXXDU
PI ~~GB 95-17371~~ A1 970326
AI GB 95-17371 950824
DT Patent
LA English
AB The invention relates to the use of aq. surfactant compn. as, or in
drilling fluids, including spacer fluids, packing fluids, or
completion fluids, wherein the compns. comprise (i) <5 wt.%
gtoreq.1 of polymeric compds., (ii) optionally, dissolved
electrolyte, (iii) <10 wt.% of surfactant, the surfactant being
present as an aq. structured surfactant, which is a soln. contg.
surfactant micelles or interspersed with a spherulitic
surfactant, in a quantity sufficient to inhibit disintegration of
shale and to maintain the rock cuttings in suspension under normal
drilling conditions, and (vi) 0-10 wt.% of a weighting agent, all
wts. being based on total wt. of the compn. A method of improving
the drilling properties of conventional unweighted water-based
drilling fluids comprising one or more polymeric compds. and
optionally dissolved electrolyte is also provided. Also drilling
fluid compns. are provided.
